

72000Q / 72003Q / 72008Q



Natural Cork Underlayment Rolls

For ceramic tile, stone, marble, glued wood flooring
and floating floor systems

FEATURES & BENEFITS:

- Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below
- Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces
- Reduces thermal transmission, increasing the effectiveness of floor heating systems
- Easy to install in both glue-down and loose lay configurations*



Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

MR 4.1 - 5% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 4.2 - 10% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.

EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)

Cork Underlayment Rolls	R-Value	Acoustical Performance	IIC	STC	Δ
72000Q - 6 mm (1/4") Quantity: 1 Roll Coverage: 200 ft ² (48" x 50')	0.74	With 6" cement slab With 6" cement slab & suspended ceiling	51 61	52 60	22
72003Q - 6 mm (1/4") Quantity: 1 Roll Coverage: 100 ft ² (48" x 25')	0.74	With 6" cement slab With 6" cement slab & suspended ceiling	51 61	52 60	22
72008Q - 3 mm (1/8") Quantity: 1 Roll Coverage: 200 ft ² (48" x 50')	0.38	With 6" cement slab & suspended ceiling	61	59	

* For a list of recommended adhesives to use for glue-down installations, please go to www.qep.com or call 866-435-8665.

E2521-10017

The Brand that Stands for Excellence.

www.QEP.com

U.S. Headquarters
866 435 8665

Canada
800 840 9422

Europe/Middle East
0031 24 6485348

Australia
011 61 3 9797 1888

New Zealand
64 9 415 9700