SECTION 1: Identification and Company Details

Product Name:	FIBERGLASS MESH SELF-ADHESIVE JOINT TAPE, CEMENT BOARD TAPE
Product Code:	GF-FT
Manufacturer/ Supplier:	QEP CO INC
Address:	1011 Broken Sound Parkway NW
Emergency Phone:	561-405-4673
Recommended Use:	Joint the Drywall/Gypsum Board/Cement Board/Wall Crack

SECTION 2: Hazard(s) Identification

Classification of the

substance or mixture: This product is not classified as hazardous under GHS criteria.

SECTION 3: Composition / Information on Ingredients

General Chemical Description:

Chemical Name Fiberglass Acrylic Acid-axrylate Percent (by weight) 68-70% 29-32% **CAS Number** 65997-17-3 25085-34-1

SECTION 4: First-Aid Measures

Inhalation: Remove to fresh air. Drink water to clear throat and blow nose to expel fibers.

Skin Contact: Wash with soap and water, remove and wash clothing before reuse. If irritation develops, get medical attention.

Eye Contact: Flush eyes with water for at least 10 minutes; Get medical assistance if irritation persists. **Ingestion:** Call MD immediately

SECTION 5: Fire-Fighting Measures

Extinguishing Media: Use that which is appropriate for surrounding fire. **Extinguishing Hazards:** None

Hazardous Combustion Products: No particular hazards known.

Protection of Firefighters: Thermal decomposition of coating material may produce an irritating mixture of smoke and fumes. Firefighters should wear full protective equipment.

SECTION 6: Accidental Release Measures

Personal Precautions: Review Section 5 and Section 7 before proceeding with clean up. Use proper personal protective equipment as indicated in Section 8.

Environmental Precautions: Do not allow product to get into drains, soil, or surface water.

Methods of Clean-up: Remove all sources of ignition. Stop leak if safe to do so. Molten / melted product should be allowed to cool and harden before cleanup.

Revision Date: 03/20/2023

SECTION 7: Handling and Storage

Handling Precautions: General Information: This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. Smoking should be prohibited in areas where this material is stored.

Handling: Avoid to storage with the corrosive and volatility solvent, and regard to water and flame. Avoid contact with eyes. Avoid ingestion.

Storage: Ventilation, dryness and moistureproof, feasible temperature is $15\sim35^{\circ}$ C, relative humidity is $30\% \sim 70\%$; the holder and support's surface is plane, not to stack on the ground, and the products packaged with paper box is not more than 1.2m, (the products packaged with air spring film and sponge paper, should be not more than 1.0m), cannot put heavy things on the products, not to tip, not to extrusion, gently take and gently put.

SECTION 8: Exposure Control / Personal Protection

Respiratory Protection: Where dust levels exceed the TLV, use NIOSH approved respirator to protect against nuisance dusts.

Ventilation: Mechanical or local exhaust to keep below TLV. **Protective Equipment:** Glove; Safety glasses.

SECTION 9: Physical and Chemical Properties

Freeze-thaw stability: -15℃ (adhesive) SRY (%): 52±1%(adhesive) Melting Point: 500℃ (fiberglass) Appearance and Odor: Woven fabric, coated, white; Slight hydrocarbon odor Boiling Point: N/A Vapor Pressure: N/A Vapor Density: N/A Softening Point: 31-33℃ (adhesive) Specific Gravity: 2.05-2.15(H2O=1) Solubility: Insoluble in water VOC:None known for fiberglass. However, Small amounts of CO2 and CO from the finish.

SECTION 10: Stability and Reactivity

Chemical Stability: Stable under normal temperature conditions and recommended use.

Conditions to Avoid: Incompatible materials, any sources of ignition or heat (e.g. open flames,

smoking, hot surfaces, excess heat).

Materials to Avoid: Avoid acid, alkali, oil and volatility solvent.

Hazardous Decomposition: Non decompounded

Hazardous Polymerization: Will not occur.

SECTION 11: Toxicological Information

Primary Route of Entry: Inhalation Effects of Overexposure: **Eyes:** Dust fibers can cause irritation. Skin: Repeated or prolonged contact may cause irritation. Ingestion: Not likely to occur Inhalation: Excessive inhalation of fibers can cause nasal and respiratory irritation. Chronic: None known Carcinogenicity of ingredients: Material NTP IARE **OSHA** Not listed Not listed Not listed Medial Condition Aggravated by Exposure: Any condition generally aggravated by mechanical irritants in air or on skin.

SECTION 12: Ecological Information

Ecological Toxicity: Not available. Persistence and degradability: Not available. Bio accumulative Potential: Not available. Mobility in Soil: Not available. Other adverse effects: Not available.

SECTION 13: Disposal Considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14: Tran	sport Information
Road:	DOT Proper Shipping Name: Non-Regulated
	DOT Packing Group: N/A
	DOT Label: N/A
	UN Number: N/A
Ocean:	Proper Shipping Name: Non-Regulated
	Sea – IMO/IMDG Class: N/A
	UN Number: N/A
	Label: N/A
	Packing Group: N/A
	Marine Pollutant: N/A
	EMS: N/A
Air:	Proper Shipping Name: Non-Regulated
	Air – ICAO/IATA Class: N/A
	UN Number: N/A
	Label: N/A
	Sub Class: N/A
	Packing Group: N/A
	Pack Instr. Passenger: N/A
	Pack Instr. Cargo: N/A

SECTION 15: Regulatory Information

Regulatory Information: Reference to the local, national, US, EU, CA and international regulations.

CAS No.	TSCA	Canada	IECSC
65997-17-3	Listed	Listed in DSL	Listed
25085-34-1	Listed	Listed in DSL	Listed

SECTION 16: Other Information

This Safety Data Sheet is prepared to comply with the GHS and United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

Prepared by: QEP CO INC

The information herein is given in good faith, but no warranty expressed or implied is made. QEP CO INC urges users of this product to evaluate its suitability and compliance with local regulations as QEP CO INC cannot foresee the final use of the product, nor the final location of usage.

Date of issue: 03/20/2022