



# Natural Cork Underlayment Sheets

## 72001Q

### INSULATING

Reduces thermal transmission, increasing effectiveness of floor heating systems

### R-Value

0.39

### SOUND ABSORBING

Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below

### IIC STC $\Delta$

71\* | 62\* | 24

\*Ceramic tile on an 8" concrete slab with a suspended ceiling

### CRACK SUPPRESSION

Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces

### NATURAL BARRIER

Cork is antimicrobial, mold and mildew resistant

### EASY TO INSTALL

In both glue-down and loose lay configurations

### VERSATILE

For use under ceramic tile, stone, marble, glued wood flooring and floating floor systems



ITEM #	DESCRIPTION	QTY	SIZE	COVERAGE
72001Q	1/2" (12 mm) Sheets	25 sheets	2' x 3'	150 sq. ft./case



Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

**MR 4.1** - 5% Recycled Content of total building materials (post consumer + 1/2 of post industrial)

**MR 4.2** - 10% Recycled Content of total building materials (post consumer + 1/2 of post industrial)

**MR 6** - Specifying rapidly renewable building materials for 5% of total building materials.

**EQ 4.1** - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)

Professional Tools. Professional Results.

qep.com

M0326-12459